

# TTPA 6000 FARM

Revised 4-19-08

1. May pull in any gear.
2. Tractor can not be over 65 HP from the factory.
3. **May run 20% over Nebraska test high idle** – PTO / Crankshaft / Flywheel speed) will be checked after pull by TTPA Tech. Inspector. It's the drivers responsibility to have reflective tape on your tractor. **See General Farm Rule # 8.**  
**3a). If the 20% over Nebraska test rule calculates / exceeds 3000 RPM's for your tractor, you are only allowed 3000 RPM's. Period.**
4. **Tire size maximum 18.4 - 38.**
5. No turbo's PERIOD.
6. No traction assist (differential lock-must remain open)
7. 4wd allowed to pull with out using front assist, 2-wheel drive only.
8. Carburetor must be the original factory as purchased housing.
9. Cut tires are allowed – top bar can be cut as desired, but you “cannot” cut or touch the front face (edge) of the lug.
10. **Five ( 5 ) MPH maximum speed limit** will be enforced by use of an electronic limiter device that triggers a loud horn.
  - A. You will be allowed Three (3) excess speed limit warning blasts of the horn after the 50 foot line. The third time even if the horn squeaks, you will be immediately disqualified. **(Note: You may blow the horn as many times as you want before reaching the 50 foot line).**
  - B. The maximum duration each time the horn blows (squawks) will be limited to three ( 3 ) seconds. **(More than three seconds gives the track official authority to immediately disqualify the contestant!).**
11. All weights must be stationary and safely secured to tractor (No Bungie Straps Allowed). If anything should fall off from the tractor (weights or parts) while hooked to the sled, you will be disqualified immediately. Front End Weights: The weight bar or weights shall not exceed more than Eleven (11) feet forward from the center of the rear axle to the furthest point forward of the tractor.
12. No age limit of tractor.
13. Vertical hooks only. The sled hooker will only hook the tractor in a vertical drop. If weights interfere with the vertical drop, you will not be hooked & will be disqualified.

14. Hitch supports are not allowed to exceed the centerline of the rear axle, **unless OEM from factory (Example Oliver 88 and Farmall M.** (See TTPA wheelie bar sketch for clarification).
15. Two (2)  $\frac{3}{4}$ " **Grade 8** bolts or, turnbuckles will be allowed to be used to the support frame, that controls the height of the primary pulling hitch
16. No turnbuckle or bolts can or, will be allowed to be fastened off the rear of the tractor and directly fastened (welded / bolted) to the Primary Pulling drawbar. (You will not be allowed to hook to the sled).
17. All general track and general farm rules apply. **(PLEASE READ THEM ALL).**

**16. RULES WILL BE ENFORCED THROUGH PULLING SEASON 2006.**

Revised 1/26/03

# 14 #15 #16 added to 6000 Farm Rules – for safety

Revised 2/21/03: weights two feet in front of tractor to, Eleven feet from rear center axle forward.

Revised 11/19/04 for 2005 / 2006 Seasons. # 3 Rule – 20% over, rather than 10% over. / # 10 Rule 4 MPH, rather than 3.5 MPH / # 10a & 10b clarification / # 14 Rule Clarification

Revised 04/19/2008 #4 changed from 16.9 tires to 18.4-38 & #10 changed from 4 mph to 5 mph.

Board approved, 1<sup>st</sup> reading 3/15/08 & 2<sup>nd</sup> reading 4/19/08.

Note: This document is deemed TTPA Copyright and is not to be copied, revised, used or changed by any other organization other than the Thumb Tractor Pulling Association Inc. without the written approved / consent of TTPA Board of Directors.